





Sphercial Roller Bearing

d 850-1120mm-249/850CA/W33249/850CAK30/W33

参数信息:



Principal dimensions ( mm ) :

|     |      |
|-----|------|
| d : | 850  |
| D : | 1120 |
| B : | 272  |

Basic load ratingsKN :

|          |       |
|----------|-------|
| dycCr :  | 8170  |
| stcCor : | 22800 |
| Pu :     | 1370  |

Speed ratingsrpm :

|                  |     |
|------------------|-----|
| Speed Ratings :  | 220 |
| Limiting Speed : | 400 |
| Weight :         | 740 |

Designation :

|                    |                           |
|--------------------|---------------------------|
| Cylindrical Bore : | 249/850C<br>A/W33         |
| Taper Bore :       | 249/850C<br>AK30/W33<br>3 |

Dimensions mm :

|        |      |
|--------|------|
| d :    | 850  |
| d ~ :  | 940  |
| D1 ~ : | 1029 |
| b :    | 22.3 |
| k :    | 12   |
| rMin : | 6    |

Abutment and fillet dimensions mm :

|          |      |
|----------|------|
| d Min :  | 873  |
| Da Max : | 1097 |
| r Max :  | 5    |



Value :

|      |      |
|------|------|
| e :  | 0.22 |
| Y1 : | 3    |
| Y2 : | 4.6  |
| Y0 : | 2.8  |



: